





BRIGHT

BRIGHT

Minimal boyut, şık tasarım ve mükemmel bir ışık: BRIGHT

Ankastre ve siva üstü aydınlatma ihtiyacını karşılamak için ufak boyutlu, verimli, şık ve yenilikçi bir aile olarak tasarlanan kare formundaki BRIGHT ailesi, boyutlarından beklenmeyen bir aydınlatma performansına ulaşıyor.

96x96 mm'den başlayan boyutlara sahip olan BRIGHT, kamaşma önleyici özel bir reflektöre ve istendiğinde kare spottan dairesel bir ışık çıkartabilecek forma sahip. Ailenin birli ve ikili ankastre versiyonları 30°'ye kadar yönlendirilebiliyor.

Vakum metalize reflektör kullanılan ve görsel konforu maksimum oranda yakalayan BRIGHT ailesinde, çerçevesiz, çerçeveli ya da IP44 korumalı gövdeler seçilebiliyor. Aileye yeni eklenen ve çerçeve ile reflektörün aynı hizada olduğu versiyonlar, alçak asma tavan uygulamaları için BRIGHT'ı vazgeçilmez bir seçenek haline getiriyor. BRIGHT'ta 6 veya 9W gücünde yüksek verimli LED ışık kaynağı kullanılıyor.

Kıscası fonksiyonellik, zarif tasarım, yüksek performans ve görsel konforun birleşimi için kare formu ile BRIGHT ailesi hizmetinizde...

Kullanım Alanları:

BRIGHT ürün ailesi; oteller, ofisler, konutlar, ticari alanlar, alışveriş merkezleri gibi mekanlarda kullanılabilir.

Minimal size, elegant design and a perfect light: BRIGHT

An innovative, chic, efficient and minimalist product family to address the lighting needs of recessed and surface mounted forms: BRIGHT. A luminaire series which performs at highest level of illumination out of its very small square shaped bodies.


BRIGHT series, featuring very small dimensions starting from 96x96 mm, has a reflector with glare shield effect and its form make possible to obtain a round form of light out of square shaped frame. Single or dual luminaires of the family could be tilted up to 30° over vertical axis.

There are framed, trimless or IP44 versions available within the series which can serve at maximum visual comfort level thanks to its vacuum metallised reflector. Recent addition of new versions to the family that frame and reflector are in the same line, make BRIGHT an indispensable option for lower suspended ceilings applications. 6 or 9W very highly efficient LED light sources are used within the family.

In summary, BRIGHT series at your service for the combination of functionality, elegant design, high performance and visual comfort.

Application Areas:

BRIGHT series can be used as decorative and functional luminaires in hotels, offices, homes, residentials, trading areas, shopping malls etc.





BRIGHT
ACIBADEM HASTANESİ- İSTANBUL



BRIGHT

ACIBADEM HASTANESİ - İSTANBUL

CIBADEM


HEALTH POINT





BRIGHT
ÜRÜN AİLESİ / PRODUCT FAMILY

BRIGHT ANKASTRE / RECESSED




BRIGHT SIVA ÜSTÜ / SURFACE MOUNTED



- Ankastrre veya siva üstü gövde seçeneđi
- Çerçevesiz, çerçevesiz, derin reflektörlü, IP44 versiyonlar
- Fonksiyonel, yenilikçi, verimli ve görsel konforlu tasarım
- 6 – 9W A+ sınıfı enerji verimli, 50.000 saat ömürlü LED
- 890 – 1.250 lümen arası (LED) ışık akısı
- 18° – 27° – 35° özel tasarım anodize metal reflektör
- 3000K - 4000K (CCT) ışık renk sıcaklığı
- DALI dim seçeneđi, otomasyona uyumlu (opsiyonel)

- Recessed and surface mounted body types
- Framed, trimless, deep reflector and IP44 versions
- Functional, innovative, efficient and comfortable design
- Class A+ energy efficient & 50.000 hours life time 6 or 9W LED power
- LED Lumen output between 890 – 1.250 lm
- Special designed anodized metal reflector with 18° – 27° – 35° beam angles
- 3000K - 4000K (CCT) light color temperature
- DALI dim option, suitable for automation (optional)



BRIGHT ANKASTRE / RECESSED



W • lm	Standard	DALI Dimm
6 W • 890 lm	L AN4213030	L AN4213040
9 W • 1250 lm	L AN4213031	L AN4213041





3000K - 4000K • 570 gr



W • lm	Standard	DALI Dimm
2x(6 W • 890 lm)	L AN4213230	L AN4213240
2x(9 W • 1250 lm)	L AN4213231	L AN4213241




3000K - 4000K • 1300 gr



W • lm	Standard	DALI Dimm
2x(6 W • 890 lm)	L AN4219230	L AN4219240
2x(9 W • 1250 lm)	L AN4219231	L AN4219241



3000K - 4000K • 1400 gr



W • lm	Standard	DALI Dimm
6 W • 890 lm	L AN4215030	L AN4215040
9 W • 1250 lm	L AN4215031	L AN4215041
IP 44 (on room side)		
6 W • 890 lm	L AN4217030	L AN4217040
9 W • 1250 lm	L AN4217031	L AN4217041




3000K - 4000K • 750 - 800 gr



BRIGHT ANKASTRE / RECESSED



18°
27°
35°



W • lm	Standard	DALI Dimm
6 W • 890 lm	L AN4216030	L AN4216040
9 W • 1250 lm	L AN4216031	L AN4216041



3000K - 4000K • 1050 gr



EAC



IP 20


850°



A+



18°
27°
35°



W • lm	Standard	DALI Dimm
6 W • 890 lm	L AN4218030	L AN4218040
9 W • 1250 lm	L AN4218031	L AN4218041



3000K - 4000K • 570 gr



EAC



IP 44


850°



A+



18°
27°
35°



W • lm	Standard	DALI Dimm
2x(6 W • 890 lm)	L AN4218230	L AN4218240
2x(9 W • 1250 lm)	L AN4218231	L AN4218241



3000K - 4000K • 1300 gr



EAC





IP 44

850°



A+

BRIGHT SIVA ÜSTÜ / SURFACE MOUNTED



W • lm	Standard	DALI Dimm
6 W • 890 lm	L SU1807030	L SU1807040
9 W • 1250 lm	L SU1807031	L SU1807041




3000K - 4000K • 1200 gr



IP 20

850°



W • lm	Standard	DALI Dimm
2x(6 W • 890 lm)	L SU1807230	L SU1807240
2x(9 W • 1250 lm)	L SU1807231	L SU1807241



3000K - 4000K • 2350 gr



IP 20

850°





BRIGHT
ACIBADEM HASTANESİ - İSTANBUL