



LAMP 83'ün endüstriyel mekanları aydınlatmak için geliştirdiği PROOFY etanj serisi, IP koruma seviyesi istenen zorlu şartlarda görev yapacak şekilde tasarlandı. Sıva üstü olarak kullanılan ürünler, IP 65 koruma seviyesine, dayanıklı polikarbon gövde ve difüzöre sahip.

PROOFY ailesinde T5 floresan lamba, G13 duylu LED tüp lamba veya LED modülü tercih etmek mümkün. LED modüllü versiyonda, ayrıca hareket sensörü kullanılarak daha da fazla bir enerji tasarrufuna ulaşılabiliyor. Ürünlerde 1 saat veya 3 saat süreli acil durum batarya kitini kullanmak da mümkün.

Endüstriyel alanınızı IP 65 korumalı PROOFY serisi ile aydınlatın ve LAMP 83'ün yüksek verimli LED teknolojisi ile tasarruf edin.

*PROOFY series, which was developed to illuminate industrial areas, is ready to perform under harsh conditions where IP protection is required. The surface mounted product series, offering IP 65 protection level as well as reliable polycarbonate body and diffuser.*

*It is possible to prefer T5 fluorescent lamp, LED tube lamp with G13 lamp holder or LED modules within the family. Moreover, PROOFY is providing more energy savings thanks to its integrated motion sensor. It is also possible to use 1 hour or 3 hours emergency battery kit with the products.*

*Illuminate your industrial areas with IP 65 PROOFY series to enjoy energy savings provided by LAMP 83's high class LED technology.*

#### Kullanım Alanları:

PROOFY ürün ailesi; IP 65 koruma seviyesi istenen iş yerlerinde, atölyelerde, depolarda, kapalı otoparklar ve fabrikalarda kullanılabilir.

#### Usage Area:

*PROOFY family is suitable to use in industrial areas, workshops, warehouses, indoor car parking areas and in factories where IP 65 protection level is required.*

#### Temel Özellikleri:

- Sıva üstü gövde
- IP 65 koruma seviyesi
- 1 saat veya 3 saat süreli acil durum batarya kiti
- T5 floresan lamba, LED tüp veya LED modül ışık kaynağı
- LED modülde hareket sensörü
- 3000K - 4000K - 6500K (CCT) ışık renk sıcaklığı

#### Basic Features:

- Surface mounted body
- IP 65 protection level
- 1 hour or 3 hours emergency battery kit
- Various light sources such as T5 fluorescent lamp, LED tube or LED module
- Motion sensor for LED modules
- 3000K - 4000K - 6500K (CCT) light color temperature



#### Etanj aydınlatma aygıtları / Waterproof luminaires



398 - 399



400 - 401



- Elektrostatik toz boyalı metal reflektör
- Polikarbon (PC) gövde
- Polikarbon veya paslanmaz çelik montaj klipsi
- Güçlendirilmiş şeffaf polikarbon diffüzör

Renk: Gri

- *Electrostatic powder coated metal reflector*
- *Polycarbonate body*
- *Polycarbonate or stainless steel mounting clips*
- *Strengthened transparent polycarbonate diffuser*

Color: Grey

LED

(LED Tube) Standard Version

Model	Power	LED Tube	Base	W	L	H	Temp
L SU3204030	1x17W	LED Tube	G13	90mm	1280mm	111mm	3000 K
L SU3204031	1x17W	LED Tube	G13	90mm	1280mm	111mm	4000 K
L SU3205030	1x25W	LED Tube	G13	90mm	1580mm	111mm	3000 K
L SU3205031	1x25W	LED Tube	G13	90mm	1580mm	111mm	4000 K

DALI DIMM Version


Model	Power	LED Tube	Base	W	L	H	Temp
L SU3204040	1x17W	LED Tube	G13	90mm	1280mm	111mm	3000 K
L SU3204041	1x17W	LED Tube	G13	90mm	1280mm	111mm	4000 K
L SU3205040	1x25W	LED Tube	G13	90mm	1580mm	111mm	3000 K
L SU3205041	1x25W	LED Tube	G13	90mm	1580mm	111mm	4000 K

Akülü; 1 saat kapasiteli / With 1 hour battery pack

Model	Power	LED Tube	Base	W	L	H	Temp
L SU3204050	1x17W	LED Tube	G13	90mm	1280mm	111mm	3000 K
L SU3204051	1x17W	LED Tube	G13	90mm	1280mm	111mm	4000 K
L SU3205050	1x25W	LED Tube	G13	90mm	1580mm	111mm	3000 K
L SU3205051	1x25W	LED Tube	G13	90mm	1580mm	111mm	4000 K

Akülü; 3 saat kapasiteli / With 3 hours battery pack

Model	Power	LED Tube	Base	W	L	H	Temp
L SU3204060	1x17W	LED Tube	G13	90mm	1280mm	111mm	3000 K
L SU3204061	1x17W	LED Tube	G13	90mm	1280mm	111mm	4000 K
L SU3205060	1x25W	LED Tube	G13	90mm	1580mm	111mm	3000 K
L SU3205061	1x25W	LED Tube	G13	90mm	1580mm	111mm	4000 K



mm.



Işık rengi Color Temperature K	Güç tüketimi Consumed power W	Lümen değeri Lumen output lm (tj:85°C)
3000	17	1660
3000	25	2950
4000	17	1750
4000	25	3100



- Elektrostatik toz boyalı metal reflektör
- Polikarbon (PC) gövde
- Polikarbon veya paslanmaz çelik montaj klipsi
- Güçlendirilmiş şeffaf polikarbon diffüzör

Renk: Gri

- *Electrostatic powder coated metal reflector*
- *Polycarbonate body*
- *Polycarbonate or stainless steel mounting clips*
- *Strengthened transparent polycarbonate diffuser*

Color: Grey

(T5) Standard Version


L	W	H	W	L	H
L SU3201001	1x28W	T5-FH	G5	W:80mm	L:1280mm H:111mm
L SU3201002	2x28W	T5-FH	G5	W:115mm	L:1280mm H:111mm
L SU3201007	1x54W	T5-FQ	G5	W:80mm	L:1280mm H:111mm
L SU3201008	2x54W	T5-FQ	G5	W:115mm	L:1280mm H:111mm
L SU3201009	1x80W	T5-FQ	G5	W:80mm	L:1580mm H:111mm
L SU3201010	2x80W	T5-FQ	G5	W:115mm	L:1580mm H:111mm

Akülü; 1 saat kapasiteli / With 1 hour battery pack

L	W	H	W	L	H
L SU3201050	1x28W	T5-FH	G5	W:80mm	L:1280mm H:111mm
L SU3201051	2x28W	T5-FH	G5	W:115mm	L:1280mm H:111mm
L SU3201056	1x54W	T5-FQ	G5	W:80mm	L:1280mm H:111mm
L SU3201057	2x54W	T5-FQ	G5	W:115mm	L:1280mm H:111mm
L SU3201058	1x80W	T5-FQ	G5	W:80mm	L:1580mm H:111mm
L SU3201059	2x80W	T5-FQ	G5	W:115mm	L:1580mm H:111mm

Akülü; 3 saat kapasiteli / With 3 hours battery pack

L	W	H	W	L	H
L SU3201060	1x28W	T5-FH	G5	W:80mm	L:1280mm H:111mm
L SU3201061	2x28W	T5-FH	G5	W:115mm	L:1280mm H:111mm
L SU3201066	1x54W	T5-FQ	G5	W:80mm	L:1280mm H:111mm
L SU3201067	2x54W	T5-FQ	G5	W:115mm	L:1280mm H:111mm
L SU3201068	1x80W	T5-FQ	G5	W:80mm	L:1580mm H:111mm
L SU3201069	2x80W	T5-FQ	G5	W:115mm	L:1580mm H:111mm



T5 Lamba renkleri / T5 Lamp colors

LM100101	T5	Soğuk beyaz / Cool white
LM100102	T5	Ilık beyaz / Warm white
LM100103	T5	Sarı / Yellow



- Elektrostatik toz boyalı metal reflektör
- Polikarbon (PC) gövde
- Polikarbon veya paslanmaz çelik montaj klipsi
- Güçlendirilmiş opak polikarbon diffüzör

Renk: Gri

- *Electrostatic powder coated metal reflector*
- *Polycarbonate body*
- *Polycarbonate or stainless steel mounting clips*
- *Strengthened opaque polycarbonate diffuser*


Color: Grey

LED

Standard Version				
L SU3208030	17,6W	LED	3000K	2500gr.
L SU3208031	17,6W	LED	4000K	2500gr.
L SU3208032	17,6W	LED	6500K	2500gr.
L SU3208033	30,6W	LED	3000K	2500gr.
L SU3208034	30,6W	LED	4000K	2500gr.
L SU3208035	30,6W	LED	6500K	2500gr.

Akülü; 1 saat kapasiteli / With 1 hour battery pack				
L SU3208050	17,6W	LED	3000K	3000gr.
L SU3208051	17,6W	LED	4000K	3000gr.
L SU3208052	17,6W	LED	6500K	3000gr.
L SU3208053	30,6W	LED	3000K	3000gr.
L SU3208054	30,6W	LED	4000K	3000gr.
L SU3208055	30,6W	LED	6500K	3000gr.

Akülü; 3 saat kapasiteli / With 3 hours battery pack				
L SU3208060	17,6W	LED	3000K	3100gr.
L SU3208061	17,6W	LED	4000K	3100gr.
L SU3208062	17,6W	LED	6500K	3100gr.
L SU3208063	30,6W	LED	3000K	3100gr.
L SU3208064	30,6W	LED	4000K	3100gr.
L SU3208065	30,6W	LED	6500K	3100gr.



Işık rengi Color Temperature K	Güç tüketimi Consumed power W	Lümen değeri Lumen output lm
3000	17,6	1900
3000	30,6	3060
4000	17,6	2000
4000	30,6	3220
6500	17,6	2000
6500	30,6	3220



LED

- Elektrostatik toz boyalı metal reflektör
- Polikarbon (PC) gövde
- Polikarbon veya paslanmaz çelik montaj klipsi
- Güçlendirilmiş opak polikarbon diffüzör
- Koridor fonksiyon özelliği

Renk: Gri

- *Electrostatic powder coated metal reflector*
- *Polycarbonate body*
- *Polycarbonate or stainless steel mounting clips*
- *Strengthened opaque polycarbonate diffuser*
- *Corridor functional featured*

Color: Grey


- Hareket varken %100 güçte çalışır, hareketin durmasından itibaren önceden belirlenmiş sürenin sonunda güç azaltımına (standby) geçer.

- *It illuminates at 100%, as long as a motion is dedected. After the motion is stopped, following a pre-determined time, the luminaire switches itself to stand-by mode.*

Standard Version				
L SU3208130	17,6W	LED	3000K	2600gr.
L SU3208131	17,6W	LED	4000K	2600gr.
L SU3208132	17,6W	LED	6500K	2600gr.
L SU3208133	30,6W	LED	3000K	2600gr.
L SU3208134	30,6W	LED	4000K	2600gr.
L SU3208135	30,6W	LED	6500K	2600gr.

Akülü; 1 saat kapasiteli / With 1 hour battery pack				
L SU3208150	17,6W	LED	3000K	3100gr.
L SU3208151	17,6W	LED	4000K	3100gr.
L SU3208152	17,6W	LED	6500K	3100gr.
L SU3208153	30,6W	LED	3000K	3100gr.
L SU3208154	30,6W	LED	4000K	3100gr.
L SU3208155	30,6W	LED	6500K	3100gr.

Akülü; 3 saat kapasiteli / With 3 hours battery pack				
L SU3208160	17,6W	LED	3000K	3200gr.
L SU3208161	17,6W	LED	4000K	3200gr.
L SU3208162	17,6W	LED	6500K	3200gr.
L SU3208163	30,6W	LED	3000K	3200gr.
L SU3208164	30,6W	LED	4000K	3200gr.
L SU3208165	30,6W	LED	6500K	3200gr.



Işık rengi Color Temperature K	Güç tüketimi Consumed power W	Lümen değeri Lumen output lm
3000	17,6	1900
3000	30,6	3060
4000	17,6	2000
4000	30,6	3220
6500	17,6	2000
6500	30,6	3220